

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Switches for appliances

Name and address of the applicant

Everel Group S.p.A.
Via Cavour, 9
37067 Valeggio sul Mincio (VR)
Italy

Name and address of the manufacturer

Everel Group S.p.A.
Via Cavour, 9
37067 Valeggio sul Mincio (VR)
Italy

Name and address of the factory

Note: When more than one factory, please report on page 2

☐ Additional information on page 2
Everel Group S.p.A.
Via Cavour, 9
37067 Valeggio sul Mincio (VR)
Italy

Ratings and principal characteristics

Switches for class II appliances; overvoltage category II;
rated impulse withstand voltage 2,5 kV; PTI250.
(see also pages from 5 to 8 of Test Report No. MI19-0046338-01 and/or
Additional Sheet)

Trademark (if any)



ED

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Series DY
(see also Additional Sheet)

Additional information (if necessary may also be reported on page 2)

☐ Additional information on page 2

A sample of the product was tested and found to be in conformity with

IEC 61058-1-1:2016, IEC 61058-1:2016

National differences:

EU Group Differences

As shown in the Test Report Ref. No. which forms part of this Certificate

MI19-0046338-01, MI19-0046338-01/1, MI19-0046338-01/2 and MI19-0046338-01/3

This CB Test Certificate is issued by the National Certification Body

IMQ S.p.A.
Via Quintiliano 43, IT-20138 Milano, Italy



Description of the switches for appliances series DY

| Type reference ⁽¹⁾ | Rated current, rated voltage and nature of supply | Code | Disconnection | Rated operating cycles | Rated ambient temperature |
|-------------------------------|---|----------------------|---------------------|------------------------|---------------------------|
| 1-DY/... | 6(2) A – 250 V ac | 1.2 bistable | Full disconnection | 1E4 | T150/55 |
| | | 1.2 momentary action | Full disconnection | | |
| 2-DY/... | | 1.3 bistable | Full disconnection | | |
| 1-DY/... | 16(6) A – 250 V ac | 1.2 bistable | Full disconnection | | T125/55 |
| | | 1.2 momentary action | Full disconnection | | |
| 2-DY/... | | 1.3 bistable | Full disconnection | | |
| | 12(4) A – 250 V ac | 1.5 bistable | Full disconnection | | |
| 1-DY/... | | 2.3 bistable | Micro disconnection | | |
| 2-DY/... | | 2.7 bistable | Micro disconnection | | |
| 1-DY/... | 6 A – 400 V ac | 1.2 bistable | Full disconnection | | |
| | | 1.2 momentary action | Full disconnection | | |
| 2-DY/... | | 1.3 bistable | Full disconnection | | |
| 1-DY/... | 6(4) A – 250 V ac | 1.2 bistable | Full disconnection | | |
| | | 1.2 momentary action | Full disconnection | | |
| | | 2.3 bistable | Micro disconnection | | |
| 2-DY/... | | 1.3 bistable | Full disconnection | | |
| | | 1.5 bistable | Full disconnection | | |
| | | 2.7 bistable | Micro disconnection | | |
| 1-DY/... | 0,02 A – 24 V dc | 1.2 bistable | Full disconnection | 5E4 | |
| | | 1.2 momentary action | Full disconnection | | |
| | | 2.3 bistable | Micro disconnection | | |
| 2-DY/... | | 1.3 bistable | Full disconnection | | |
| | | 1.5 bistable | Full disconnection | | |
| | | 2.7 bistable | Micro disconnection | | |
| 1-DY/... | 10(4) A – 250 V ac | 1.2 bistable | Full disconnection | | |
| | | 1.2 momentary action | Full disconnection | | |
| | | 2.3 bistable | Micro disconnection | | |
| 2-DY/... | | 1.3 bistable | Full disconnection | | |
| | | 1.5 bistable | Full disconnection | | |
| | | 2.7 bistable | Micro disconnection | | |

⁽¹⁾ – The description of the type reference is given on page 2

Description of the type reference of the switches for appliances series DY

- DY /

Characteristics:

Number from 1 to 999 indicating the characteristics of the switch, such as wiring diagram, ratings, colour of the body, etc.

Basic reference of the series:

DY

Number of poles:

1 = 1 pole

2 = 2 poles