



# 产品认证证书

证书编号: CQC15002123227

## 申请人名称及地址

Everel Group S. p. A.  
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), 意大利

## 制造商名称及地址

Everel Group S. p. A.  
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), 意大利

## 生产企业名称及地址

EVEREL ROMANIA SRL (V021291)  
Loc. Lipova Str. TIMISORII, Nr.109 315400 Arad, 罗马尼亚

## 产品名称和系列、规格、型号 器具开关

A1, A2, A4 (具体型号规格详见附件) IP40 耐热3级 PTI250 锡焊端子 插片端子 污染等级2

## 产品标准和技术要求

GB15092.1-2010

## 认证模式

产品型式试验+初次工厂检查+获证后监督

上述产品符合CQC11-462124-2009认证规则的要求, 特发此证。

发证日期: 2015年05月12日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

主任: \_\_\_\_\_



# 中国质量认证中心

中国·北京·南四环西路188号9区100070

<http://www.cqc.com.cn>

C 0070375



# PRODUCT CERTIFICATE

No.: CQC15002123227

## NAME AND ADDRESS OF THE APPLICANT

Everel Group S.p.A.  
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), Italy

## NAME AND ADDRESS OF THE MANUFACTURER

Everel Group S.p.A.  
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), Italy

## NAME AND ADDRESS OF THE FACTORY

EVEREL ROMANIA SRL (V021291)  
Loc.Lipova Str.TIMISORII,Nr.109 315400 Arad,ROMANIA

## NAME, MODEL AND SPECIFICATION

Switch for Appliances

A1, A2, A4 (具体型号规格详见附件) IP40 耐热3级 PTI250 锡焊端子 插片端子 污染等级2

## THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB15092.1-2010

## CERTIFICATION MODEL

Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned products have met the requirements of certification rules CQC11-462124-2009.

Date of issue: May.12,2015

Validity of this certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

President:

  
Wang Kejiao



## CHINA QUALITY CERTIFICATION CENTRE

Section 9, No.188, Nansihuan Xilu, Beijing 100070 P.R.China  
<http://www.cqc.com.cn>

C 0070375



# 产品认证证书

附录:

证书编号: CQC15002123227

第 1 页 共 1 页

纸号: 70375

具体规格如下:

Rated voltage AC	A1		A2		A4	
	Rated current	Operating cycles	Rated current	Operating cycles	Rated current	Operating cycles
250 V	3 (1) A	10E3	3 (1) A	10E3	3 (1) A	10E3
	6 (2) A	10E3	6 (2) A	10E3	6 (2) A	10E3
	10 (2) A	10E3	10 (2) A	10E3	10 (2) A	10E3
	10 (4) A	10E3	10 (4) A	10E3	10 (4) A	10E3
	13 (4) A	10E3	13 (4) A	10E3	13 (4) A	10E3
	6 (6) A	10E3/50E3	-	-	-	-
	1 (0,05) A	50E3	1 (0,05) A	50E3	1 (0,05) A	50E3
	3 (1) A	50E3	3 (1) A	50E3	3 (1) A	50E3
	6 (1) A	50E3	6 (1) A	50E3	6 (1) A	50E3
	6 (4) A	50E3	6 (4) A	50E3	6 (4) A	50E3
400 V	-	-	-	-	6 A	10E3
Type and construction of switches	Rocker switch continuous contact code: 1.2(1.2 NO or 1.2 NC) momentary contact code: 2.3, 3.3 code 1.2 optional with signal indicator		Rocker switch continuous contact code: 1.2, 2 x 1.2 NO,NC momentary contact code: 2.3, 3.3 code 1.2 and 2 x 1.2 optional with signal indicator		Rocker switch continuous contact code: 1.2, 1.3, 2.3, 2 x 2.3, 2 x 3.3 momentary contact code: 1.2, 1.3, 2.3, 2 x 2.3, 2 x 3.3 code 1.3 optional with signal indicator	

General:

Ambient air temperature	direct actuating 125 / 55 °C	Circuit disconnection	Micro disconnection Only 6 (4)A, 13 (4)A
	indirect actuating 125 °C		Full disconnection
			The other types

主任: \_\_\_\_\_

注: 此附录与证书同时使用时有效。

## 中国质量认证中心

中国·北京·南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>

