



GP



C **UL** US



TYPICAL APPLICATIONS

Vacuum and steam cleaners

FUNCTIONS

- SPST
- DPST, illuminated or not

CYCLE No.

50.000

CUT OUT

19x13 mm

AMBIENT TEMPERATURE

125 °C

GWT

850 °C

GWT NO FLAME (<2 sec)

750 °C on demand

G

P





DRAWING




TERMINAL




WATERPROOF CAP








1




3



7





Z	Y	X
0,7 ... 1,25	13,0 ±0,1	19,1 ±0,1
1,25 ... 2,0	13,0 ±0,1	19,4 ±0,1
2,0 ... 3,0	13,0 ±0,1	19,7 ±0,1

G

P

M

0

0

TERMINAL

FUNCTION

RATING

BODY COLOUR

ROCKER COLOUR

MARKING COLOUR

MARKING COLOUR

FUNCTION

1

2

8

RATING

H

12 A / 250 VAC
6 (6) A / 250 VAC
2 / 120A - 250 VAC
5 (5) A / 250 VAC - 5E4
T125/55 °C
EN 61058-1

15 A GP / 125 VAC
12 A GP / 250 VAC
6 (6) A / 250 VAC
T105/55 °C
UL 61058-1

BODY COLOUR

1

black

2

white

X

?

custom

ROCKER COLOUR

1

black

2

white

ILLUMINATED

G

red

H

orange

E

green

X

?

custom

MARKING COLOUR

0

none

1

black

2

white

8

red

X

?

custom

MARKING

0

1

4

6

R

X